

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L22	11	(first near (coil or impedance or inductor or inductive)) with (capacitor or capacitance) with between with (second near (coil or impedance or inductor or inductive)) same (op\$1amp or opamp or operational \$1amplifier or operational \$1amplifier or (operational near amplifier))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/24 11:32
L13	22	((first or input) near (coil or impedance)) with (capacitor or capacitance) with between with ((second or output) near (coil or impedance)) same (op\$1amp or opamp or operational \$1amplifier or operational \$1amplifier or (operational near amplifier))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/24 10:45

L12	9	(first near (coil or impedance)) with (capacitor or capacitance) with between with (second near (coil or impedance)) same (op\$1amp or opamp or operational \$1amplifier or operational \$1amplifier or (operational near amplifier))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/24 10:44
L11	3	(first near coil) with (capacitor or capacitance) with between with (second near coil) same (op\$1amp or opamp or operational \$1amplifier or operational \$1amplifier or (operational near amplifier))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/24 10:43
L10	2	(first near coil) with (capacitor or capacitance) with between with (second near coil) same (frequency \$1response or (frequency near response))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/24 10:42
L8	22	(first near coil) near3 (capacitor or capacitance) near2 between near3 (second near coil)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/24 10:07
S64	3	((coil or impedance) near2 first) same ((coil or impedance) near2 second) same (capacitor or capacitance) and S62	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:51

S63	9	(combine or combin\$3 or add or composite) with ((direct \$1current or (direct near current) or "DC") near (term or component)) with (direct\$1current or (direct near current) or "DC") near2 (voltage or bias) and S52	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:49
S61	13	((coil or impedance) near2 first) same ((coil or impedance) near2 second) same (capacitor or capacitance) and (op\$1amp or opamp or (operational near amplifier)) and ((composite or combining) near2 circuit)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:44
S60	2	((coil or impedance) near2 first) same ((coil or impedance) near2 second) same (capacitor or capacitance) and (op\$1amp or opamp or (operational near amplifier)) same ((composite or combining) near2 circuit)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:44

S59	2	((coil or impedance) near2 first) same ((coil or impedance) near2 second) same (capacitor ro capacitance) and (op\$1amp or opamp or (operational near amplifier)) same ((composite or combining) near2 circuit)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:43
S58	2	((coil or impedance) near2 first) same ((coil or impedance) near2 second) same (capacitor ro capacitance) and (op\$1amp or opamp or (operational near amplifier)) same ((composite or combining) near circuit)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:43
S57	2	((coil or impedance) near2 first) with ((coil or impedance) near2 second) same (capacitor or capacitance) same between) same (op\$1amp or opamp or (operational near amplifier)) and ((composite or combining) near circuit)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:21

S56	3	((coil or impedance) near2 first).clm. and ((coil or impedance) near2 second).clm. and capacitor.clm. and (op\$1amp or opamp or (operational near amplifier)).clm. and ((composite or combining) near circuit)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:20
S55	1	((coil or impedance) near2 first).clm. and ((coil or impedance) near2 second).clm. and capacitor.clm. and (op\$1amp or opamp or (operational near amplifier)).clm. and (pulse \$1pattern or ((pulse or signal) near (pattern or generat\$3))) and ((composite or combining) near circuit)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:20
S54	1	((coil or impedance) near2 first).clm. and ((coil or impedance) near2 second).clm. and capacitor.clm. and (op\$1amp or opamp or (operational near amplifier)).clm. and (pulse \$1pattern or ((pulse or signal) near (pattern or generat\$3))) and S52	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:19

S52	11699	(375/239 375/130 375/135 375/146 375/295-296 375/309 375/312 375/377 375/316-319 702/66).ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:18
S48	117	Shiratsuchi near Satoru Fujinuma near Kazuhiro Saito near Sumio AOBA near WATARU	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 16:06
S41	101	((coil or impedance) near2 first) with ((coil or impedance) near2 second) with (capacitor or capacitance) with between) and (op \$1amp or opamp or (operational near amplifier))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 15:47
S40	3	((coil or impedance) near2 first).clm. and ((coil or impedance) near2 second).clm. and capacitor.clm. and (op\$1amp or opamp or (operational near amplifier)).clm. and (offset near (adjust or adjustment or adjusting))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 15:46
S39	1	((coil or impedance) near2 first).clm. and ((coil or impedance) near2 second).clm. and capacitor.clm. and (op\$1amp or opamp or (operational near amplifier)).clm. and S35	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 15:44

S38	1	((coil or impedance) near2 first).clm. and ((coil or impedance) near2 second).clm. and capacitor.clm. and (op\$1amp or opamp or (operational near amplifier)).clm. and (pulse \$1pattern or ((pulse or signal) near (pattern or generat\$3))) and S35	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 15:44
S24	17	((coil or impedance) near2 first) with ((coil or impedance) near2 second) with capacitor with between) same (op\$1amp or opamp or (operational near amplifier))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT	OR	ON	2009/03/23 15:32

3/ 24/ 2009 11:58:26 AM

C:\ Documents and Settings\ svlahos\ My Documents\ EAST\ Workspaces\ 10579385.wsp